

BIPRO

96-cell

SYSTEM & PRODUCT CERTIFICATES

CUL US LISTED CE





PERFORMANCE WARRANTY











16BB Half-cut Cell Technology



Industry Leading High Yield



Excellent Anti-PID Performance



Wider Application



IP68 Junction Box

ELECTRICAL CHARACTERISTICS

Testing Condition	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (Pmax/W)		 		 		 		 		
Operating Voltage (Vmpp/V)		1		1		1		1		
Operating Current (Impp/A)		 		 		 		 		
Open-Circuit Voltage (Voc/V)		1		1		1		1		
Short-Circuit Current (Isc/A)		I I		I I		I I I		I I		
Module Efficiency (%)										

STC: Irradiance $1000W/m^2$, Spectra at AM1.5, Module Temperature $25\,^{\circ}$. Power output tolerance: $0\sim+5W$, Test uncertainty for Pmax: $\pm3\%$ NMOT: Irradiance $800W/m^2$, Spectra at AM1.5, Ambient Temperature $20\,^{\circ}$, Wind speed 1m/s


REAR SIDE POWER GAIN(REFERENCE TO 445W FRONT)

Pmax gain			
Pmax/W			
Vmpp/V			
Vmpp/V Impp/A			
Voc/V			
Isc/A			

MECHANICAL CHARACTERISTICS

Cell Type	
No. of Cells	
Module Dimensions	
Weight	
Front Glass	
Back Glass	
Frame	
Junction Box	
Output Cables	2
Connectors	

Electrical Performance



APPLICATION CONDITIONS

Maximun System Voltage	
Operating Temperature	
Maximun Series Fuse	
Safety Protection Class	П
Mechanical Load	
Refer. Bifaciality Factor	±

TECHNICAL DRAWINGS

TEMPERATURE CHARACTERISTICS

Temperature Coefficient of Pmax	
Temperature Coefficient of Voc	
Temperature Coefficient of Isc	
Nominal Module Operating Temperature(NMOT)	±

PACKING CONFIGURATION

Pieces Per Pallet	
Pieces Per Container(40'HQ)	

