



保证功率

84.8%

5

	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
(Pmax/W)	350	261	355	264	360	267	365	271	370	275
(Vmpp/V)	33.7	31.1	34.0	31.4	34.3	31.6	34.6	31.9	34.9	32.1
(Impp/A)	10.40	8.37	10.45	8.43	10.50	8.46	10.56	8.50	10.61	8.55
(Voc/V)	40.3	37.5	40.5	37.7	40.7	37.9	40.9	38.0	41.1	38.2
(Isc/A)	11.04	8.91	11.10	8.96	11.15	9.00	11.20	9.04	11.26	9.09
(%)	19.20		19.50		19.70		20.00		20.30	
STC	1000W/m <sup>2</sup> ,		AM1.5,		25		0~+5W		± 3%	
NMOT(	800W/m <sup>2</sup>		AM1.5		20		1m/s			

	9BB
	120 (6*20)
	1755*1038*30mm (69.09*40.87*1.18 )
	19.5kg (42.99lbs)
	3.2mm
	IP68, 3
	4mm <sup>2</sup> (IEC), 12AWG(UL) 300mm
	T01/LJQ-3-CSY/MC4/MC4-EVO2

	1000V/1500V/DC
	-40°C~+85°C
	20A
	Class
	5400Pa
	2400Pa

Pmax	-0.36%/°C
Voc	-0.26%/°C
Isc	+0.043%/°C
NMOT	43± 2°C

	36	36(USA)
(40'HC)	988	936

## I-V

